iiyama | Entry Series

An ultra fast 2 millisecond response time coupled with a sleek and stylish black or silver cabinet ensures that iiyama's 17-inch ProLite E1702S and new 19-inch E1902S bring a host of advance features to your fingertips at an affordable price.

	ProLite E1702S	ProLite E1902S
Panel	TN	TN
Diagonal	17'' (43 cm)	19'' (48 cm)
Display area h x w	270.3 x 337.9 mm	301.1 x 376.3 mm
Response time	5 ms	2 ms
Contrast ratio	1000 : 1 typical	1000 : 1 typical
Brightness	300 cd/m² typical	300 cd/m² typical
Viewing zone (CR>10)	horizontal/vertical: 160°/160° right/left: 80°/80° up/down: 80°/80°	horizontal/vertical: 160°/160° right/left: 80°/80° up/down: 80°/80°
Display colour	16.7 mln	16.7 mln
Native resolution	1.3 MegaPixel (1280 x 1024)	1.3 MegaPixel (1280 x 1024)
Input connector	DVI-D, D-Sub	DVI-D, D-Sub
Speaker	2 x 1 W (Stereo)	2 x 1 W (Stereo)
Weight	4.1 kg	4.9 kg
Dimensions w x h x d	370.5 x 381.5 x 210 mm	407.5 x 407 x 210 mm
Colours	black, white, silver	black, white, silver
Cables included	power cable, D-Sub signal cable, DVI-D signal cable, audio cable	power cable, D-Sub signal cable, DVI-D signal cable, audio cable

iiyama | Business Series | Height Adjustable

Top-class features are what first catch the eye in iiyama's business models. These displays deliver best-in-class performance in every respect. Graphic artists, CAD and DTP users who settle for nothing but the best will value the sRGB and gamma correction functions that permit even the finest nuances of colour to be set accurately.

	ProLite B1702S	ProLite B1902S
Panel	TN	TN
Diagonal	17'' (43 cm)	19'' (48 cm)
Display area h x w	270.3 x 337.9 mm	301.1 x 376.3 mm
Response time	5 ms	2 ms
Contrast ratio	1000 : 1 typical	1000 : 1 typical
Brightness	300 cd/m² typical	300 cd/m² typical
Viewing zone (CR>10)	horizontal/vertical: 160°/160° right/left: 80°/80° up/down: 80°/80°	horizontal/vertical: 160°/160°; right/left: 80°/80°; up/down: 80°/80°
Display colour	16.7 mln	16.7 mln
Native resolution	1.3 MegaPixel (1280 x 1024)	1.3 MegaPixel (1280 x 1024)
Input connector	D-Sub, DVI-D	D-Sub, DVI-D
Speaker	2 x 1 W (Stereo)	2 x 1 W (Stereo)
Height Adjustment	110 mm	110 mm
Weight	5.5 kg	6 kg
Dimensions w x h x d	370.5 x 397 (507) x 236.5 mm	407.5 x 393 (503) x 236.5 mm
Colours	black, white	black, white
Cables included	power cable, D-Sub signal cable, DVI-D signal cable, audio cable	power cable, D-Sub signal cable, DVI-D signal cable, audio cable

Ideal for home and business applications iiyama's Wide Screen LCDs are ground breaking products. They lend themselves to a wide variety of applications due to an incredible specification and extensive feature set. The breadth of product enables real choice with uncompromising quality.

CERTIFIED FOR Windows Vista®

	ProLite E1902WSV	ProLite E2003WS/E2003WSV
Panel	TN	TN
Diagonal	19'' (48 cm)	20.1" (51.1 cm)
Display area h x w	256.5 x 410 mm	270.9 x 433.4 mm
Response time	2 ms	2 ms
Contrast ratio	1000 : 1 typical	2000 : 1 DCR
Brightness	400 cd/m² typical	300 cd/m² typical
Viewing zone (CR>10)	horizontal/vertical: 170°/160° right/left: 85°/85° up/down: 80°/80°	horizontal/vertical: 170°/170° right/left: 85°/85° up/down: 85°/85°
Display colour	16.7 mln	16.7 mln
Native resolution	1.3 MegaPixel (1440 x 900)	1.8 MegaPixel (1680 x 1050)
Input connector	D-Sub	D-Sub, DVI-D*
Speaker	2 x 1 W (Stereo)	2 x 1 W (Stereo)
Weight	4.3 kg	4.4 kg
Dimensions w x h x d	438.5 x 363 x 210 mm	480 x 399 x 188 mm
Colours	black, silver	black
Cables included	power cable, D-Sub cable, audio cable	power cable, D-Sub cable, DVI-D signal cable*, audio cable

* available only for ProLite E2003WS

	ProLite E2201W	ProLite E2202WS/E2202WSV
Panel	TN	TN
Diagonal	22'' (56 cm)	21.6" (55 cm)
Display area h x w	296.1 x 473.8 mm	290.6 x 464.9 mm
Response time	2 ms	5 ms
Contrast ratio	1000 : 1 typical	1000 : 1 typical
Brightness	300 cd/m² typical	300 cd/m² typical
Viewing zone (CR>10)	horizontal/vertical: 170°/160° right/left: 85°/85° up/down: 80°/80°	horizontal/vertical: 160°/160° right/left: 80°/80° up/down: 80°/80°
Display colour	16.7 mln	16.7 mln
Native resolution	1.8 MegaPixel (1680 x 1050)	1.8 MegaPixel (1680 x 1050)
Input connector	D-Sub, DVI-D	D-Sub, DVI-D*
Speaker	-	2 x 2W (Stereo)
Weight	5.8 kg	5.0 kg
Dimensions w x h x d	507 x 410.5 x 209.5 mm	506 x 404 x 210 mm
Colours	black	black
Cables included	power cable, D-Sub signal cable, DVI-D signal cable	power cable, DVI-D signal cable*, D-Sub signal cable, audio cable

* available only for ProLite E2202WS

	ProLite E2403WS	Height Adjustable ProLite B2403WS
Panel	TN	TN
Diagonal	24'' (61.2 cm)	24'' (61.2 cm)
Display area h x w	324 x 518.4 mm	324 x 518.4 mm
Response time	2 ms	2 ms
Contrast ratio	2000 : 1 DCR	2000 : 1 DCR
Brightness	250 cd/m² typical	300 cd/m² max
Viewing zone (CR>10)	horizontal/vertical: 170°/160° right/left: 85°/85° up/down: 85°/75°	horizontal/vertical: 170°/160° right/left: 85°/85° up/down: 85°/75°
Display colour	16.7 mln	16.7 mln
Native resolution	2.3 MegaPixel (1920 x 1200)	2.3 MegaPixel (1920 x 1200)
Input connector	D-Sub, HDMI	D-Sub, HDMI
Speaker	2 x 2 W (Stereo)	2 x 2 W (Stereo)
Height Adjustment	-	130 mm
Rotation (Pivot)	-	90°
Weight	6.5 kg	8.7 kg
Dimensions w x h x d	566 x 458.5 x 191.5	566 x 445 (575) x 220 mm
Colours	black	black
Cables included	power cable, D-Sub signal cable, DVI-HDMI cable, audio cable	power cable, D-Sub signal cable, DVI-HDMI cable, audio cable

iiyama | LCD TV

ProLite C1900WTV is a 19" WideScreen solution with superb specifications. The C1900WTV boasts an array of inputs, including the popular HDMI for connectivity to performance graphics cards, games consoles and even set top boxes. Auto station tuning, fast text and various picture format support adds to the superb TV quality achieved by the product. A real high quality, high performance, fully featured LCDTV.

	ProLite C1900WTV
Panel	TN
Diagonal	19'' (48 cm)
Display area h x w	256.5 x 410.4 mm
Response time	5 ms
Contrast ratio	1000 : 1 typical
Brightness	400 cd/m² typical
Viewing zone (CR>10)	horizontal/vertical: 170°/160° right/left: 85°/85° up/down: 80°/80°
Display colour	16.7 mln
Native resolution	1.3 MegaPixel (1440 x 900)
Input connector	D-Sub mini 15, HDMI, Antenna, Composite RCA SCART, YPbPr component, Audio
Teletext	Simple-Text, TOP-Text, Fast-Text
Standard TV	PAL, SECAM, NTSC
Picture formats	Full, Normal, Panorama, Zoom1, Zoom2, WSS
Speaker	2 x 2.5 W (Stereo)
Weight	4.95 kg
Dimensions w x h x d	443 x 379.7 x 210 mm
Colours	black
Cables included	power cable, D-Sub signal cable, audio cable (PC), RCA A/V cable, HDMI cable